



Declaration of Performance

In accordance with the (EU) standard no. 305/2011 dated 09 March 2011

N° 2013CERVOG001

- 1) Unique product identification code
Dry-pressed ceramic tiles with low water absorption $0.5\% < E_b \leq 3\%$
- 2) Intended use
For interior and exterior floors and walls
- 3) Name or registered trademark and manufacture's address
Ceramica Vogue - Via Papa Giovanni XXIII, 100 Loc. Vergnasco - 13882 Cerrione (BI)
- 4) System of Assessment and Verification of Constancy of Performance (AVCP)
System 4
- 5) Name and identification number of the notified laboratory, if applicable
Not applicable
- 6) Declared performance

Main features	Performance	Harmonized technical specification
Reaction to fire	A1/A1 _{FL}	EN 14411
Release of dangerous substances		
Cadmium	NDP	
Lead	NDP	
Tensile strength	≥ 1700 N thickness $\geq 7,5$ mm	
	≥ 1000 N thickness $< 7,5$ mm	
Slipperiness	NDP	
Adhesion force	NDP	
Resistance to thermal shock	Resistant	
Durability for:		
Internal use	Resistant	
External use	NDP	
VOC	A+	

The performance of the product identified in paragraph 1 complies with the performance declared under point 6. This Declaration of Performance is issued under the sole responsibility of the manufacturer identified in point 3.

Vittuone, 10 October 2017

Alberto Bardelli (CEO)



Declaration of Performance

In accordance with the (EU) standard no. 305/2011 dated 09 March 2011

N° 2013CERVOG002

- 1) Unique product identification code
Dry-pressed ceramic tiles Eb>10%
- 2) Intended use
For interior and exterior floors and walls
- 3) Name or registered trademark and manufacture's address
Ceramica Vogue - Via Papa Giovanni XXIII, 100 Loc. Vergnasco - 13882 Cerrione (BI)
- 4) System of Assessment and Verification of Constancy of Performance (AVCP)
System 4
- 5) Name and identification number of the notified laboratory, if applicable
Not applicable
- 6) Declared performance

Main features	Performance	Harmonized technical specification
Reaction to fire	A1/A1 _{FL}	EN 14411
Release of dangerous substances		
Cadmium	NDP	
Lead	NDP	
Tensile strength	NDP	
Slipperiness	NDP	
Adhesion force	NDP	
Resistance to thermal shock	Resistant	
Durability for:		
Internal use	Resistant	
External use	NDP	
VOC	A+	

The performance of the product identified in paragraph 1 complies with the performance declared under point 6. This Declaration of Performance is issued under the sole responsibility of the manufacturer identified in point 3.

Vittuone, 10 October 2017

Alberto Bardelli (CEO)

